


# LFP Series Wide Opening Fork Positioners

- Allows fork positioning wider than the clamp body
- Clean, grease-free handling — no lubrication required
- High net truck capacity; weld-on forks for added strength
- Flow divider for even fork movement
- Repair-N-Place serviceability



## Non-Sideshifting Fork Positioners, 1 Function

Model Number	Capacity <sup>1</sup> lb @ 24"	Range <sup>2</sup> ITO (in)	Fork Size T x W x L (in)	Mounting Class	Body Width (in)	Lost Load AET (in)	HCG (in)	VCG (in)	Weight (lb)
LFP-35NN-FB536			1.5 x 5 x 36				6.0	8.5	785
LFP-35NN-FB542	3,500	14.0-70.4	1.5 x 5 x 42	II	36	7.0	7.0	8.2	810
LFP-35NN-FB548			1.5 x 5 x 48				8.2	7.8	840
LFP-45NN-FB536			1.5 x 5 x 36				5.8	8.7	805
LFP-45NN-FB542	4,500	14.0-75.4	1.5 x 5 x 42	II/III	41	7.0	6.9	8.4	830
LFP-45NN-FB548			1.5 x 5 x 48				8.0	8.0	860
LFP-55NN-FC536			1.75 x 5 x 36				6.1	9.0	855
LFP-55NN-FC542	5,500	14.0-75.0	1.75 x 5 x 42	II/III	41	7.3	7.3	8.4	875
LFP-55NN-FC548			1.75 x 5 x 48				8.3	8.2	915
LFP-70NN-FD542			2 x 5 x 42				7.2	8.5	920
LFP-70NN-FD548	7,000	17.0-81.0	2 x 5 x 48	III	41	7.5	8.5	8.8	955
LFP-70NN-FD554			2 x 5 x 54				9.8	7.7	990
LFP-7DNN-FD542			2 x 5 x 42				5.7	8.9	1,320
LFP-7DNN-FD548	7,000	15.0-98.4	2 x 5 x 48	III	62	8.0	6.6	8.6	1,355
LFP-7DNN-FD554			2 x 5 x 54				7.6	8.4	1,390
LFP-85NP-FD648			2 x 6 x 48	III or IV			7.3	9.9	1,805
LFP-85NP-FD654	8,500	22-97.8	2 x 6 x 54	III or IV	50	9.8	8.3	9.0	1,845
LFP-85NP-FD660			2 x 6 x 60	III or IV			8.7	9.3	1,890
LFP-10NP-FD648			2 x 6 x 48	III or IV			6.8	9.3	1,995
LFP-10NP-FD654	10,000	22-109.8	2 x 6 x 54	III or IV	62	9.8	7.7	9.0	2,035
LFP-10NP-FD660			2 x 6 x 60	III or IV			8.6	8.8	2,080
LFP-15NP-FF648	15,000	22-103.8	2.5 x 6 x 48	IV	56		Consult factory for specifications and price		

<sup>1</sup> Carrying capacity only. Do NOT use as a clamp. See Section E, pages E-10 to E-12 for pallet fork clamps.

<sup>2</sup> Minimum fork spread range is to inside of forks. Maximum fork spread range is to outside of forks.

## Minimum Truck Carriage Width

Model Number	Body Width (in)	Minimum Truck Carriage Width (in)
LFP-35	36	30
LFP-45/55/70	41	35
LFP-7D	62	39
LFP-85 ITA III	50	35
LFP-85 ITA IV	50	42
LFP-10	62	42
LFP-15	56	36

## Recommended Hydraulic Supply

Model Number	Flow (gpm)	Max psi
LFP-35/45	7-10	2,000
LFP-70/7D	7-10	2,000
LFP-85/10/15	9-15	2,000

Hydraulic flow less than minimum may reduce operating speed and/or cause irregular arm movement. Higher flow may result in heat build-up, erratic operation and shortened hydraulic system life.

See page B-6 for Optional Mounting Hooks and Optional Features.