


LFP Series Wide Opening Fork Positioners

- Allows fork positioning wider than the clamp body
- Clean, grease-free handling — no lubrication required
- High net truck capacity; weld-on forks for added strength
- Flow divider for even fork movement
- Repair-N-Place serviceability



Non-Sideshifting Fork Positioners, 1 Function

Model Number	Capacity ¹ lb @ 24"	Range ² ITO (in)	Fork Size T x W x L (in)	Mounting Class	Body Width (in)	Lost Load AET (in)	HCG (in)	VCG (in)	Weight (lb)
LFP-35NN-FB536	3,500	14.0–70.4	1.5 x 5 x 36	II	36	7.0	6.0	8.5	785
LFP-35NN-FB542			1.5 x 5 x 42				7.0	8.2	810
LFP-35NN-FB548			1.5 x 5 x 48				8.2	7.8	840
LFP-45NN-FB536	4,500	14.0–75.4	1.5 x 5 x 36	II/III	41	7.0	5.8	8.7	805
LFP-45NN-FB542			1.5 x 5 x 42				6.9	8.4	830
LFP-45NN-FB548			1.5 x 5 x 48				8.0	8.0	860
LFP-55NN-FC536	5,500	14.0–75.0	1.75 x 5 x 36	II/III	41	7.3	6.1	9.0	855
LFP-55NN-FC542			1.75 x 5 x 42				7.3	8.4	875
LFP-55NN-FC548			1.75 x 5 x 48				8.3	8.2	915
LFP-70NN-FD542	7,000	17.0–81.0	2 x 5 x 42	III	41	8.6	7.8	8.0	935
LFP-70NN-FD548			2 x 5 x 48				8.9	7.7	970
LFP-70NN-FD554			2 x 5 x 54				10.3	7.3	1,000
LFP-7DNN-FD542	7,000	15.0–98.4	2 x 5 x 42	III	62	9.0	5.6	9.0	1,340
LFP-7DNN-FD548			2 x 5 x 48				7.5	8.7	1,385
LFP-7DNN-FD554			2 x 5 x 54				8.5	8.4	1,410
LFP-85NP-FD648	8,500	22–97.8	2 x 6 x 48	III or IV	50	9.8	7.3	9.9	1,805
LFP-85NP-FD654			2 x 6 x 54				8.3	9.0	1,845
LFP-85NP-FD660			2 x 6 x 60				8.7	9.3	1,890
LFP-10NP-FD648	10,000	22–109.8	2 x 6 x 48	III or IV	62	9.8	6.8	9.3	1,995
LFP-10NP-FD654			2 x 6 x 54				7.7	9.0	2,035
LFP-10NP-FD660			2 x 6 x 60				8.6	8.8	2,080
LFP-15NP-FF648	15,000	22–103.8	2.5 x 6 x 48	IV	56	Consult factory for specifications and price			

¹ Carrying capacity only. Do NOT use as a clamp. See Section E, pages E-10 to E-12 for pallet fork clamps.

² Minimum fork spread range is to inside of forks. Maximum fork spread range is to outside of forks.

Optional Mounting Hooks for LFP Models

Model Number	Description
Class II	Quick change hooks
Class III	Quick change hooks
Class IV	Quick change hooks

Recommended Hydraulic Supply

Model Number	Flow (gpm)	Max psi
LFP-35/45	7-10	2,000
LFP-70/7D	7-10	2,000
LFP-85/10/15	9-15	2,000

Hydraulic flow less than minimum may reduce operating speed and/or cause irregular arm movement. Higher flow may result in heat build-up, erratic operation and shortened hydraulic system life.

See page B-6 for Optional Features.