


All-In-One Pulp/Paper Clamps

- Interchangeable, slip-on arms for versatility
- Quad Pack and Twin Pack configurations
- Handles pulp bales with pulp bale arms
- Clean, grease-free handling — no lube arm slides



Sideshifting All-in-One Clamps (Non-Rotating), 2 Functions

Model Number	Model Type	Paper Rolls			Pulp Bales			Mounting Class	Weight (lb)	
		Capacity (lb @ LC, in)	Roll Range 2 Rolls (in)	Roll Range 1 Roll (in)	Capacity (lb @ 35")	Opening Range (in)	Arm Size H x L (in)			
NSQ-75NS-QPP51	Quad Pack	7,500 @ 30	2 x (34–51)	34–60	6,500	34–108	18 x 48	III	2,535 ¹ 2,615 ²	
NSQ-88NS-QPP45		8,800 @ 30	2 x (30–45)	34–51	8,800	28–88	20 x 48	III or IV	2,675 ¹ 2,795 ²	
NSQ-88NS-QPP51		8,800 @ 30	2 x (31–51)	34–60	8,800	34–108	20 x 48	III or IV	3,240 ¹ 3,260 ²	
NSQ-88NS-QPP53		8,800 @ 30	2 x (32–53)	32–60	8,800	32.5–110	20 x 55	III or IV	3,375 ¹ 3,425 ²	
NSQ-11NS-QPP51		11,000 @ 30	2 x (34–51)	34–60	11,000	34–108	20 x 48	IV	3,580 ¹ 3,650 ²	
NSQ-11NS-QPP53		11,000 @ 30	2 x (32–53)	32–60	11,000	32.5–111	20 x 55	IV	3,715 ¹ 3,815 ²	
NSQ-11NS-TPP51		Twin Pack	11,000 @ 30	2 x (34–51)	34–60	11,000	34–108	20 x 48	IV	3,480 ¹ 3,650 ²

¹ Weight with paper roll arms.

² Weight with pulp bale arms (Quad Pack model shown)

Optional Equipment

Model Number	Item
YL-279	Single setting relief valve
2528295	Single setting relief valve, 3600 psi max
YL-354	Three position relief valve
2520877	Pressure gauge
YSVK-1	Solenoid installation kits ¹ , 1 - 2 functions
2527912	Set of 2 quick disconnect hydraulic couplings ²
Y088122.1	Control knob – 2 functions (1 button)
	Bumper pad
YCSY-0234-CLCTM	Clamp force gauge, 10,000 lbs max. psi
YCSY-0428-CLCTM	Clamp force gauge, 30,000 lbs max. psi
2518127	Cart kit, for use with clamp force gauges

¹ Includes the hoses and fittings to connect a standard attachment to the hose terminal on the lift truck carriage.

² See page J-3 for more information on quick disconnect coupling kits.

Installation Equipment

Model Number	Item
YHJL-8-D-30 ¹	Jump lines: 2 functions, #8 hose

¹ Includes the hoses and fittings to connect a standard attachment to the hose terminal on the lift truck carriage.

Optional Mounting Hooks

	Description
Class III	Quick change hooks
Class IV	Quick change hooks
Class III/IV	Dual bolt-on hooks
Class III/IV	Dual quick change hooks
Pin/shaft mounting	