





A Modern, Self Propelled Baler

Based on the Legendary Freeman side-feed Baler, Designed and Built in the United States.

Best in the field.

Baler SpecificationsModel:280,*285380,*385

Chamber Size:			
Cross Section		16" x 22" (41x56 cm) - standard	
	16" x 18" (41x46 cm) - standard	15" x 22" (38x56 cm) - standard	
	14" x 18" (36x46 cm) - optional	14" x 22" (36x56 cm) - optional	
		14" x 21" (36x53 cm) - optional	
Length	18" to 52"	18" to 52"	
Weight Range	60 to 120 lbs	90 to 180 lbs	
Tension Control	3-cylinder hydraulic - standard	tandard 3-cylinder hydraulic - standard	
Chamber Length	9´ x 0´´ (275 cm) - standard	9´ x 0″ (275 cm) - standard	
Rated Capacity	25 tons/hour (alfalfa)	30 tons/hour (alfalfa)	
	25.4 mt/hour	30.48 mt/hour	

Pickup:		
Width	70" (178 cm) - standard	
Width w/flares	76" (193 cm) - standard	
Drive	Chain	
Number of Teeth	156 on 2-1/2" centers on 6 tooth bars	

Plunger:		
Stroke Length	30" (76.2 cm) - standard	
Strokes per minute (normal under load)	84	
Rollers	Sealed Ball-Bearing Rollers (bottom) Wear Pads (top)	

Power:		
4 Cylinder Engine	John Deere Turbo Charged POWERTECH 4.5L 99 hp (86 kW)	
Fuel Tank	30 gal (114 ltr) standard	

Baler Dimensions:						
Overall Length	21´ 6″ (6.55 m)	21´6″ (6.55 m)				
Overall Width	12´ 2″ (3.71 m)	12´ 10″ (3.91 m)				
Overall Height	11´0″ (3.35 m)	10´ 10″ (3.30 m)				
Weight 14,000 lbs (6350 kg)		15,500 lbs (7030 kg)				

* Tail-Less Twine Knotter

Freeman Factory				
21433 SW Oregon Street Sherwood, OR 97140 USA	Phone: Fax:	503.625.2560 800.285.7000 503.625.5132 800.231.3273	E-mail: Web:	marketing@alliedsystems.com service@alliedsystems.com parts@alliedsystems.com www.alliedsystems.com
Freeman Baler Parts & S	ervice			
1662 Zenos Rd Holtville, CA 92250	Phone: Fax:	760.756.3080 760.756.3044		

You need a baler that works day in, day out. No baler on the market matches the Freeman side feed baler for performance or longevity. Now, you get all the advantages of the Freeman, in a fully redesigned, self propelled version.

The spacious cab provides unparalleled comfort and visibility, while the powerful and efficient John Deere engine keeps you moving. At the heart of the machine is the Freeman side feed baler, with generations of know-how built in.

Available tail-less knotters keep your field clean of string trimmings. An onthe-go moisture sensor and bale scale provide instant feedback, so you know your bales are just right.

The Freeman self propelled side feed baler. No compromises. *Best in the field*.