

Engine, Cummins QSX15

Description: Cummins Electronic QS Series Engine

Specifications: QSX15-C525 Industrial Engine. Rated 525 HP @2100 rpm, Intermittent Duty Cycle, Repto Pump Drive, Dry Flywheel Housing, A/C Compressor Bracket Provided.

Cummins Option	Description
AB1010	Accessory Support
AP1045	Certified EPA, CARB, EU, Off-Highway Tier II
BR1241	Crankcase Breather Plumbing, Open, LH Side
CF1023	Mounting Pad for A/C Compressor, Engine RH Side
CH1014	Block Heater, w/o Cord, 120 VAC, 1500 Watt
CS1066	Cold Start Option, Uses 3681138 Ether Kit
DF1020	No front Drive
DL1047	Fuel Drain Line, Engine LH Center, 7/8-14 UNF SAE 45 Deg Seat
EB1203	Non-Engine Brake
EH1033	Alternator Mounting, Engine RH Side
EM1343	Front Engine Mount, Ductile Cast Iron, 2-Hole TBA (Fan Drive Option)
FF1254	Fuel Filter, Single, Direct Mount w/ WIF, LH Center
FH11104	Flywheel Housing, REPTO, Single C-Drive Ear, RH Side, Rear
FR10377	Fuel Rating, 525 HP Int. @2100 RPM, 1800 ft-lb @ 1400 RPM Peak HP 578 @ 1800 RPM
FS1068	Fuel Priming Pump, Electric, Mounted on Fuel Rail Body
FW1022	Flywheel, SAE 1, For Clark 5000/8000 Torque Converter/Trans
IC1065	Air Intake Manifold Connection 90 Deg, Forward Facing, 4.0" OD
IT1021	Turbo Compressor Outlet, 90 Deg, 4.0" OD
LF1210	Full Flow/Bypass Lube Oil Filter, Spin On, Engine RH Side, on Cooler
LG1085	Dipstick, Intake Side of Engine
OB1400	Oil Fill, Engine RH Side, Below Crankshaft Centerline
OP1491	Front Sump Oil Pan, Stamped Steel
PW1060	Programable Power
SP1062	3" fan Spacer Group, Consists of 2.5" and .5" Spacers
SS1139	Black Pain, Cummins Spec 21076
ST1334	Starting Motor, Delco Remy 42MT400, 24 VDC, for 6/8 Pitch Ring Gear
SV1002	24VDC Engine Operating Voltage
TB1412	Turbo Arrangement, Los, Center Mounted, Exh. To Rear, for CAC Systems
TH1160	Thermostat Housing Cover
VC1072	Valve Cover
WF1241	Cooling System Corrosion Inhibitor, WF2126 Element
WI1087	Water Inlet Connection, 2.5" OD, 90 Deg, Pointing Down
WO1123	Water Outlet Connection, 2.5" OD, Pointing Up
XS1059	Exhaust Outlet Connection, 90 Deg, Half Marmon, w/Test Port, 5.75" OD