

Maintenance Checklists

Periodic scheduled maintenance is intended to be performed in a complete maintenance facility by trained mechanics. Scheduled maintenance procedures can be found by referring to the appropriate section of the service manual.

Always refer to manufacture's (e.g. engine, transmission, axle) maintenance manual before performing any maintenance.

First Shift (10 Hours)

Perform these checks after the first shift, or after 10 hours, whichever occurs first.

1	Check torque of expander pins. See form 80-1124 in Service Manual.	OK <input type="checkbox"/>	No <input type="checkbox"/>
---	--	-----------------------------	-----------------------------

First 50 Hours

These checks should be performed after the machine has been in service for 50 hours.

1	Check fluid levels - differential, planetaries	OK <input type="checkbox"/>	Add <input type="checkbox"/>
2	Check hydraulic system - hoses, fittings	OK <input type="checkbox"/>	Repair <input type="checkbox"/>
3	Check battery - cables & connections	OK <input type="checkbox"/>	Repair <input type="checkbox"/>
4	Check all driveline capscrews - torque to spec. See service forms 80-1057 Torque Specification Chart & 80-627 Driveline Service.	OK <input type="checkbox"/>	No <input type="checkbox"/>
5	Check electrical system - lights, options, connections	OK <input type="checkbox"/>	No <input type="checkbox"/>
6	Check all pins, bushings and load bearing hardware	OK <input type="checkbox"/>	No <input type="checkbox"/>
7	Check accumulator pre-charge (see 80-1076)	OK <input type="checkbox"/>	No <input type="checkbox"/>
8	Check parking brake lining wear and readjust if necessary	OK <input type="checkbox"/>	Readjust <input type="checkbox"/>
9	Check torque of expander pins. See form 80-1124 in Service Manual.	OK <input type="checkbox"/>	No <input type="checkbox"/>

MECHANIC _____

SUPERVISOR _____

DATE _____

MODEL _____

SERIAL No _____

HOUR METER _____

First 100 Hours

These checks should be performed after the machine has been in service for 100 hours.

1	Drain, flush and fill differential	OK <input type="checkbox"/>	No <input type="checkbox"/>
2	Drain, flush and fill planetaries	OK <input type="checkbox"/>	No <input type="checkbox"/>
3	Inspect wheel bearing preload, readjust if necessary	OK <input type="checkbox"/>	No <input type="checkbox"/>
4	Change transmission filters	OK <input type="checkbox"/>	No <input type="checkbox"/>

Weekly Maintenance (50 Hours)

Perform these checks weekly, or after 50 hours, whichever occurs first.

1	Repeat the 10 hour check	OK <input type="checkbox"/>	No <input type="checkbox"/>
2	Check for fluid leaks - oil, fuel, water, transmission	OK <input type="checkbox"/>	Repair <input type="checkbox"/>
3	Check battery electrolyte level	OK <input type="checkbox"/>	Add <input type="checkbox"/>
4	Lubricate chassis & driveline cross assemblies	OK <input type="checkbox"/>	No <input type="checkbox"/>
5	Record engine rpm	High <input type="text"/>	Stall <input type="text"/>
6	Check for structural damage - inspect chassis & attachments for bending, cracking & broken welds	OK <input type="checkbox"/>	Repair <input type="checkbox"/>

Bi-Weekly Maintenance (100 Hours)

Perform these checks every other week, or after 100 hours, whichever occurs first.

1	Check wheel lug nuts and studs mechanically, check torque	OK <input type="checkbox"/>	Repair <input type="checkbox"/>
---	---	-----------------------------	---------------------------------

MECHANIC

SUPERVISOR

DATE

MODEL

SERIAL No

HOURLY METER

Monthly Maintenance (250 Hours)

Perform these checks monthly, or after 250 hours, whichever occurs first.

1	Repeat the 100 hour check	OK <input type="checkbox"/>	No <input type="checkbox"/>
2	Take engine oil sample for analysis	OK <input type="checkbox"/>	No <input type="checkbox"/>
3	Check axle differential oil level	OK <input type="checkbox"/>	Add <input type="checkbox"/>
4	Check axle planetary oil levels	OK <input type="checkbox"/>	Add <input type="checkbox"/>
5	Change fuel filter	OK <input type="checkbox"/>	Add <input type="checkbox"/>
6	Change coolant filter	OK <input type="checkbox"/>	Add <input type="checkbox"/>
7	Change hydraulic tank breather assembly	OK <input type="checkbox"/>	No <input type="checkbox"/>
8	Check all hydraulic pressures and record	OK <input type="checkbox"/>	No <input type="checkbox"/>
9	Check fire suppression actuator	OK <input type="checkbox"/>	No <input type="checkbox"/>
10	Check supplemental coolant additive (SCA) and Antifreeze Concentration	OK <input type="checkbox"/>	No <input type="checkbox"/>
11	Check engine wiring harness	OK <input type="checkbox"/>	No <input type="checkbox"/>
12	Check pump mounting bolts and hose connections. Re-torque if necessary.	OK <input type="checkbox"/>	No <input type="checkbox"/>
13	Check and adjust the parking brake	OK <input type="checkbox"/>	No <input type="checkbox"/>
14	Check torque of expander pins. See form 80-1124 in Service Manual.	OK <input type="checkbox"/>	No <input type="checkbox"/>

MECHANIC _____

SUPERVISOR _____

DATE _____

MODEL _____

SERIAL No _____

HOUR METER _____

Quarterly Maintenance (500 Hours)

Perform these checks quarterly, or after 500 hours, whichever occurs first.

1	Repeat the 250 hour check	OK <input type="checkbox"/>	No <input type="checkbox"/>
2	Change engine oil & filters	OK <input type="checkbox"/>	No <input type="checkbox"/>
3	Change high pressure hydraulic filters	OK <input type="checkbox"/>	No <input type="checkbox"/>
4	Change hydraulic return filters	OK <input type="checkbox"/>	No <input type="checkbox"/>
5	Change brake cooling return filters	OK <input type="checkbox"/>	No <input type="checkbox"/>
6	Take oil samples from transmission, axle, and hydraulic system for analysis	OK <input type="checkbox"/>	No <input type="checkbox"/>
7	Check accumulator pre-charge pressure (see 80-1076 in Service Manual)	OK <input type="checkbox"/>	No <input type="checkbox"/>
8	Check AC system components (see 80-1082 in Service Manual)	OK <input type="checkbox"/>	No <input type="checkbox"/>

MECHANIC _____

SUPERVISOR _____

DATE _____

MODEL _____

SERIAL No _____

HOUR METER _____

Semi-Annual Maintenance (1000 Hours)

Perform these checks semi-annually, or after 1000 hours, whichever occurs first.

1	Repeat the 500 hour check	OK <input type="checkbox"/>	No <input type="checkbox"/>
2	Change transmission oil and filter elements	OK <input type="checkbox"/>	No <input type="checkbox"/>
3	Clean and flush cooling system	OK <input type="checkbox"/>	No <input type="checkbox"/>
4	Drain, flush and fill differential	OK <input type="checkbox"/>	No <input type="checkbox"/>
5	Drain, flush and fill planetaries	OK <input type="checkbox"/>	No <input type="checkbox"/>
6	Check pins and bushings for wear	OK <input type="checkbox"/>	No <input type="checkbox"/>
7	Steam clean machine, inspect for structural cracks	OK <input type="checkbox"/>	No <input type="checkbox"/>
8	Replace cab pressurizer and air recirculation elements.	OK <input type="checkbox"/>	No <input type="checkbox"/>
9	Drivelines - See service form 80-627, Driveline Service & Maintenance.	OK <input type="checkbox"/>	No <input type="checkbox"/>
10	Have ANSUL representative inspect and recertify fire suppression system	OK <input type="checkbox"/>	No <input type="checkbox"/>
11	Inspect AC system components (see 80-1082 in Service Manual)	OK <input type="checkbox"/>	No <input type="checkbox"/>

MECHANIC _____

SUPERVISOR _____

DATE _____

MODEL _____

SERIAL No _____

HOUR METER _____

Every 1,500 Hours, or 1 Year

Perform these checks at 1500 hours, or 1 year, whichever occurs first. Perform all previous maintenance procedures that are due for scheduled maintenance.

1	Adjust overhead set, engine	OK <input type="checkbox"/>	No <input type="checkbox"/>
2	Check radiator assembly	OK <input type="checkbox"/>	No <input type="checkbox"/>
3	Check water pump, engine	OK <input type="checkbox"/>	No <input type="checkbox"/>
4	Check cooling system hoses	OK <input type="checkbox"/>	No <input type="checkbox"/>
5	Check batteries	OK <input type="checkbox"/>	No <input type="checkbox"/>
6	Check turbo charger	OK <input type="checkbox"/>	No <input type="checkbox"/>
7	Check engine Mounts	OK <input type="checkbox"/>	No <input type="checkbox"/>

Annual Maintenance (2000 Hours)

Perform these checks annually, or after 2000 hours, whichever occurs first.

1	Repeat the 1,000 hour check	OK <input type="checkbox"/>	No <input type="checkbox"/>
2	Change hydraulic oil	OK <input type="checkbox"/>	No <input type="checkbox"/>
3	Drivelines - Inspect slip splines for wear (backlash). See service form 80-627, Driveline Service & Maintenance	OK <input type="checkbox"/>	No <input type="checkbox"/>
4	Check wet disc brake lining wear	OK <input type="checkbox"/>	No <input type="checkbox"/>
5	Inspect wheel bearing preload, readjust if necessary	OK <input type="checkbox"/>	Readjust <input type="checkbox"/>
6	Have Allied representative inspect machine (annually)	OK <input type="checkbox"/>	No <input type="checkbox"/>
7	Replace AC Receiver-Drier (see 80-1082 in Service Manual)	OK <input type="checkbox"/>	No <input type="checkbox"/>

MECHANIC _____

SUPERVISOR _____

DATE _____

MODEL _____

SERIAL No _____

HOUR METER _____

Every 6,000 Hours, or 2 Years

Perform these checks at 6000 hours, or 2 years, whichever occurs first. Perform all previous maintenance procedures that are due for scheduled maintenance.

1	Check vibration dampener, engine	OK <input type="checkbox"/>	No <input type="checkbox"/>
2	Check fan drive pulley assembly, engine	OK <input type="checkbox"/>	No <input type="checkbox"/>
3	Check fan hub, engine	OK <input type="checkbox"/>	No <input type="checkbox"/>
4	Check air compressor discharge lines	OK <input type="checkbox"/>	No <input type="checkbox"/>

Overhaul Schedule

To maximize efficiency and minimize downtime and costly failures, Allied Systems Company recommends the following overhaul chart to be used. When followed closely, your equipment will last longer with less unexpected downtime. Contact your local Wagner dealer for the kits necessary to overhaul your drivetrain components or allow your dealer to overhaul the components for you. They are authorized to overhaul and test your components.

It is recommended that some components be overhauled at the same time, even if they might have some time before their required rebuild, to minimize downtime. Many components may have to be removed in order to gain access to others so the parts should all be rebuilt together. This will save you from having to tear the machine down again a few thousand operation hours later.

During the overhaul process, make sure all parts are thoroughly cleaned before installation. Parts that do not receive this cleaning can cause the lubricant to become contaminated, which leads to much shorter service life.



CAUTION

The overhaul schedule below is applicable when all preventive maintenance and oil testing is performed and only when genuine Wagner OEM replacement parts and lubricants are used. Major component overhauls may need to be performed more frequently if preventive maintenance is not performed, non-OEM replacement parts are used, and/or the machine is operated frequently on slopes, uneven terrain, or in poor traction conditions.

Component	Hours
Engine	20,000
Transmission	20,000
Converter	10,000
Pumps	10,000
Axle	20,000
Brakes	20,000*
Hydraulic Cylinders - Reseal	10,000
Hoses and Fittings	20,000

* Or sooner if indicated during 2,000 hour wear check.

MECHANIC _____

SUPERVISOR _____

DATE _____

MODEL _____

SERIAL No _____

HOUR METER _____

INTENTIONALLY LEFT BLANK