## **H5C Hydraulic Winch**

#### **Recommended Service Parts**

The following pages list some of the service parts and kits that are available for your Allied H5C Winch.

Page 1 includes a Filter Kit. The filter element should be changed after the first 250 hours, then every 500 hours thereafter. Keep this kit in stock at all times for regular maintenance.

Pages 1 and 2 contains kits for 5,000 hour and 10,000 hour scheduled maintenance. Order these kits from the tables when you are in preparation for these intervals. Page 2 also contains a list of wire rope assemblies for you to order as required.

Page 3 contains lists of handlever installation components, tool kits, and specialized tools. Order parts or tools as required, and as relevant for your installation.

Page 4 contains a list of diagnostic tools, which are useful when you install, maintain and service your winches.

Note: Allied winch parts manuals are available for no charge download at http://www.alliedsystems.com/pubs/pubs.htm.

Filter Kit, P/N 2304112W - High Performance Winch: H5CH**K37 & H5CH**C80					
Service Interval: First 250 hours, then every 500 hours					
Allied P/N	Description	Quantity on Winch	See Parts Manual Page	Order Quantity	
2304112W	Filter, Element	1	Hydraulic Group		

**Note**: For all other Hi-Performance (H) winches and Rescue (T) winches, please refer to dozer operator's manuals, use tractor filters.

### Motor, Reducer & Brake Assembly Rebuild Kit, P/N 2311895

#### Service Interval: Every 5,000 hours

Allied P/N	Description	Quantity on Winch	See Parts Manual Page	Order Quantity	
2311895	Kit, Motor, Reducer & Brake Assembly Rebuild	1			
12916W	. Ring, Snap	2	Motor Shaft		
12944W	. Ring, Snap	1	Motor Shaft		
2306073W	. Seal, Rotary	2	Hydraulic Group		
89776W	. O-Ring	3	Hydraulic Group		
86596W	. O-Ring	1	Hydraulic Group		
87287W	. O-Ring	1	Motor Shaft		
334475W	. Ring, Snap	1	Motor Shaft		
12944W	. Ring, Snap	1	Motor Shaft		
246722	. Kit, Seal	1	Hydraulic Motor		

86-607 1 Rev. 10/31/2012



ntermediate, Idler, Drum Shaft, Motor & Brake Assembly Rebuild Kit, P/N 2311896					
ervice Inter	val: Every 10,000 hours				
Allied P/N	Description	Quantity on Winch	See Parts Manual Page	Order Quantity	
2311896	Kit, Intermediate, Idler, Drum Shaft, Motor & Brake Assembly Rebuild	1			
41207W	. Bearing, Ball	1	Motor Shaft		
41210W	. Ring, Snap	1	Motor Shaft		
2306198W	. Disc, Friction	7	Motor Shaft		
2304874W	. Plate, Separator	8	Motor Shaft		
218214	. O-Ring	1	Intermediate Gear Shaft		
212380	. O-Ring	1	Intermediate Gear Shaft		
159940W	. O-Ring	1	Intermediate Gear Shaft		
2305923W	. Cone, Roller Bearing	1	Intermediate Gear Shaft		
45733W	. Cup, Roller Bearing	1	Intermediate Gear Shaft		
219114W	. Cone, Roller Bearing	1	Intermediate Gear Shaft		
2302515W	. Cup, Roller Bearing	1	Intermediate Gear Shaft		
133523W	. Seal, Oil	1	Drum Shaft		
339681W	. Seal, Oil	1	Drum Shaft		
219093W	. Cone, Roller Bearing	1	Drum Shaft		
219094W	. Cup, Roller Bearing	1	Drum Shaft		
12956W	. Ring, Snap	2	Drum Shaft		
219095W	. Bearing, Roller	1	Drum Shaft		
203533	. O-Ring	1	Drum Shaft		
2304580W	. Bearing, Cylinder Roller	1	Idler Shaft		
41207W	. Bearing, Ball	1	Idler Shaft		
12916W	. Ring, Snap	1	Idler Shaft		

Wire Rope A	ssemblies	Order	as Required	
Allied P/N	Description	Length	Will Fill Drum To	Order Quantity
WR5-279L	Wire Rope Assembly, 5/8"	279' (85 M)	2/3 Capacity (recommended)	
WR5-423L	Wire Rope Assembly, 5/8"	423' (129 M)	Full Capacity	
WR6-197L	Wire Rope Assembly, 3/4"	197' (60 M)	2/3 Capacity (recommended)	
WR6-298L	Wire Rope Assembly, 3/4"	296 ' (91 M)	Full Capacity	
WR7-142L	Wire Rope Assembly, 7/8"	142' (43 M)	2/3 Capacity (recommended)	
WR7-215L	Wire Rope Assembly, 7/8"	215' (66 M)	Full Capacity	
YS7-215LWS	Wire Rope Assembly, 7/8"	215' (66 M)	Full Capacity	



Handlever Installation Components			Order	as Required
Allied P/N	Description	Quantity on Winch	Relevant for Installation	Order Quantity
250589	Coil, Solenoid	1	John Deere 750J	
2307231W	Kit, Seal	1	John Deere 750J	
2310013	Assembly, Switch - 24V W/Yellow LED	varies	All	
2310504	Assembly, Switch - W/Lock , 24V W/Red LED	1	Caterpillar D6K & Komatsu D51-22	
2310506	Assembly, Switch - Momentary, 24V W/Red LED	1	John Deere 700J	
R13661	Relay	1	John Deere 750J	

Tool Kits	Orde	er as Required	
Order these Tool Kits as required for installation, maintenance and service of your winch(es).			
Allied P/N	Description	Order Quantity	
588466	Socket Set, 3/8DR 3/8" to 7/8" STD/Deep, 22 PC		
588467	Socket Set, 1/2DR 3/8" to 1-1/4" STD/Deep, 30 PC		
588468	Socket Set, 3/4DR 7/8" to 2-3/8" STD, 29 PC		
588469	Wrench Set, 5/16" to 2-1/2", 31 PC		
588527	Hex Key Sets, .025" to 5/8", 18 PC		
588530	Socket Sets, 3/8DR 6mm-19mm 12 Point		
588529	Socket Sets, 1/2DR 10mm-26mm 12 Point		
588528	Wrench Sets, 7mm-24mm, 18 PC		
588526	Hex Key Sets, .07mm-17mm, 15 PC		

Specialized Tools Ord		der as Required	
Order these specialized tools for installation, maintenance and service of your winch(es).			
Allied P/N	Description	Order Quantity	
X-201962	Lifting Device		
X-203345	Clutch Shaft Locknut Socket		
X-203346	Clutch Shaft Driver		
X-203348	Lifting Eye		


86-607 3 Rev. 10/31/2012



### Diagnostic Tools\* Order as Required

Order these Tools as required for maintenance and service of your winch(es).

Allied P/N	Description	Order Quantity
906601	0 to 8700 PSI Digital Pressure Gauge W/Female QD Connector	
69782	72" Hose Assembly W/QD Connectors Both Ends	
70381	144" Hose Assembly W/QD Connectors Both Ends	
69778	Multi-Meter, 12 Function	





Duty Cycle Non-Contact


InfraRed Thermometer

CAT III Test Leads

Type K Bead Wire Temp Probe







#### Note: The following items are specially necessary for H5C winch(es) mounted on Komatsu D51-22.

Alli	ied P/N	Description	Order Quantity
23	310634	1/4 NPT Male QD	
2	54002	Test Fitting	
23	310365	Test Fitting	
23	310250	1/4 NPT Female Coupling - w/o Valve	