


LCC ADJUST-A-FORCE™ Carton Clamps

- Clean, grease-free handling, patented Repair-N-Place serviceability
- Provides “soft touch” to handle the most delicate products
- Exclusive spring plate arms distribute force evenly over load support area



Sideshifting Carton Clamps, 2 Functions

Model Number	Capacity lbs @ LC (in)	Opening Range (in)	Arm Size L x H (in)	Mounting Class	Lost Load AET (in)	HCG (in)	VCG (in)	Weight (lbs)
LCC-25NS-S4048	2,500 @ 20	21.0–75.5	40 x 48	II	5.0	13.0	13.6	1,181
LCC-25NS-S4248	2,500 @ 21		42 x 48			13.5	13.7	1,200
LCC-25NS-S4648	2,500 @ 23		46 x 48			14.3	13.8	1,228
LCC-25NS-S4848	2,500 @ 24		48 x 48			15.5	13.8	1,294
LCC-35NS-S4048	3,500 @ 20	21.0–75.5	40 x 48	II	5.0	12.6	13.5	1,223
LCC-35NS-S4248	3,500 @ 21		42 x 48			13.1	13.5	1,242
LCC-35NS-S4648	3,500 @ 23		46 x 48			13.9	13.7	1,270
LCC-35NS-S4848	3,500 @ 24		48 x 48			15.1	13.7	1,336
LCC-35NS-S5248	3,230 @ 26	21.0–75.5	52 x 48	II	5.0	16.0	13.8	1,364
LCC-35NS-S5448	3,110 @ 27		54 x 48			16.2	14.9	1,490
LCC-35NS-S4054	3,500 @ 20		40 x 54			13.2	14.5	1,255
LCC-35NS-S4254	3,500 @ 21		42 x 54			13.8	14.6	1,275
LCC-35NS-S4654	3,500 @ 23	21.0–75.5	46 x 54	II	5.0	14.6	14.9	1,310
LCC-35NS-S4854	3,500 @ 24		48 x 54			15.6	14.9	1,375
LCC-35NS-S5254	3,230 @ 26		52 x 54			16.5	15.0	1,407
LCC-35NS-S5454	3,110 @ 27		54 x 54			18.5	15.0	1,534
LCC-35NS-S4060	3,500 @ 20	21.0–75.5	40 x 60	II	5.0	13.3	15.6	1,288
LCC-35NS-S4260	3,500 @ 21		42 x 60			13.9	15.8	1,310
LCC-35NS-S4660	3,500 @ 23		46 x 60			14.8	16.1	1,345
LCC-35NS-S4860	3,500 @ 24		48 x 60			16.0	16.1	1,415
LCC-35NS-S5260	3,230 @ 26	21.0–75.5	52 x 60	II	5.0	17.0	16.3	1,450
LCC-35NS-S5460	3,110 @ 27		54 x 60			18.9	16.3	1,580
LCC-50NS-S4248	5,000 @ 21		42 x 48			13.0	13.5	1,265
LCC-50NS-S4648	5,000 @ 23		46 x 48			13.7	13.6	1,295
LCC-50NS-S4848	5,000 @ 24	21.0–75.5	48 x 48	II or III	5.0	14.9	13.6	1,360
LCC-50NS-S4060	5,000 @ 20		40 x 60			13.2	15.5	1,316
LCC-50NS-S4260	5,000 @ 21		42 x 60			13.7	15.7	1,334
LCC-50NS-S4660	5,000 @ 23		46 x 60			14.6	16.0	1,369
LCC-50NS-S4860	5,000 @ 24	48 x 60	15.8	16.0	1,438			

Lower Mounting Hooks

Model Number	Mounting Class	Angle (°)	Description
ANO	II	0	Bolt-on
AQO			Quick change
BNO	III	0	Bolt-on
BQO			Quick change

Installation Kits

Model Number	Number of Functions
YHJL-6-D-30	2
YHJL-8-D-30	

Includes the hoses to connect a standard attachment to the hose terminal on the lift truck carriage.

Minimum Truck Carriage Width

Model Number	Body Width (in)	Minimum Truck Carriage Width (in)
LCC-25/35/50	41	35

Recommended Hydraulic Supply

Model Number	Flow (gpm)	Max psi
All Models	7–9	2,500

Hydraulic flow less than minimum may reduce operating speed and/or cause irregular arm movement. Higher flow may result in heat build-up, erratic operation and shortened hydraulic system life.