

#### **Maintenance Checklists**

Periodic scheduled maintenance is intended to be performed in a complete maintenance facility by trained mechanics. Scheduled maintenance procedures can be found by referring to the appropriate section of the service manual.

Always refer to manufacture's (e.g. engine, transmission, axle) maintenance manual before performing any maintenance.

#### **First 50 Hours**

These checks should be performed after the machine has been in service for 50 hours.

1	Check fluid levels - differential, planetaries	ок 🗖	Add 🗖
2	Check hydraulic system - hoses, fittings	ок 🗖	Repair 🗖
3	Check battery - cables & connections	ок 🗖	Repair 🗖
4	Check all driveline capscrews - torque to spec. See service forms 80-1057 Torque Specification Chart & 80-627 Driveline Service.	ок 🗖	No 🗖
5	Check electrical system - lights, options, connections	ок 🗖	No 🗖
6	Check all pins, bushings and load bearing hardware	ок 🗖	No 🗖
7	Check accumulator pre-charge (see 80-1076)	ок 🗖	No 🗖
8	Check parking brake lining wear and readjust if necessary	ок 🗖	Readjust 🗖

#### First 100 Hours

These checks should be performed after the machine has been in service for 100 hours.

1	Drain, flush and fill differential	ок 🗖	No 🗖
2	Drain, flush and fill planetaries	ок 🗖	No 🗖
3	Inspect wheel bearing preload, readjust if necessary	ок 🗖	No 🗖
4	Change transmission filters	ок 🗖	No 🗖

MECHANIC	
SUPERVISOR	
DATE	
MODEL	
SERIAL No	
HOUR METER	

## Weekly Maintenance (50 Hours)

Perform these checks weekly, or after 50 hours, whichever occurs first.

1	Repeat the 10 hour check	ОК 🗖	No 🗖
2	Check for fluid leaks - oil, fuel, water, transmission	ок 🗖	Repair 🗖
3	Check battery electrolyte level	ок 🗖	Add 🗖
4	Lubricate chassis & driveline cross assemblies	ок 🗖	No 🗖
5	Record engine rpm	High	Stall
6	Check for structural damage - inspect chassis & attachments for bending, cracking & broken welds	ок 🗖	Repair 🗖

# **Bi-Weekly Maintenance (100 Hours)**

Perform these checks every other week, or after 100 hours, whichever occurs first.

1	Check wheel lug nuts and studs mechanically, check torque	ок 🗖	Repair 🗖
---	---	------	----------

MECHANIC	
SUPERVISOR	
DATE	
MODEL	
SERIAL No	
HOUR METER	

### <u>Wagner</u>

# **Monthly Maintenance (250 Hours)**

Perform these checks monthly, or after 250 hours, whichever occurs first.

1	Repeat the 100 hour check	ок 🗖	No 🗖
2	Take engine oil sample for analysis	ок 🗖	No 🗖
3	Check axle differential oil level	ок 🗖	Add 🗖
4	Check axle planetary oil levels	ок 🗖	Add 🗖
5	Change fuel filter	ок 🗖	Add 🗖
6	Change coolant filter	ок 🗖	Add 🗖
7	Check all hydraulic pressures and record	ок 🗖	No 🗖
8	Check fire suppression actuator	ок 🗖	No 🗖
9	Check supplemental coolant additive (SCA) and Antifreeze Concentration	ок 🗖	No 🗖
10	Check engine wiring harness	ок 🗖	No 🗖
11	Check pump mounting bolts and hose connections. Re-torque if necessary.	ок 🗖	No 🗖
12	Check and adjust the parking brake	ок 🗖	No 🗖

MECHANIC	
SUPERVISOR	
DATE	
MODEL	
SERIAL No	
HOUR METER	

# **Quarterly Maintenance (500 Hours)**

Perform these checks quarterly, or after 500 hours, whichever occurs first.

1	Repeat the 250 hour check	ок 🗖	No 🗖
2	Change engine oil & filters	ок 🗖	No 🗖
3	Change high pressure hydraulic filters	ок 🗖	No 🗖
4	Change hydraulic return filters	ок 🗖	No 🗖
5	Take oil samples from transmission, axle, and hydraulic system for analysis	ок 🗖	No 🗖
6	Check accumulator pre-charge pressure (see 80-1076)	ок 🗖	No 🗖

MECHANIC	
SUPERVISOR	
DATE	
MODEL	
SERIAL No	
HOUR METER	

#### <u>Wagner</u>

# Semi-Annual Maintenance (1000 Hours)

Perform these checks semi-annually, or after 1000 hours, whichever occurs first.

1	Repeat the 500 hour check	ок 🗖	No 🗖
2	Change transmission oil and filter elements	ок 🗖	No 🗖
3	Clean and flush cooling system	ок 🗖	No 🗖
4	Drain, flush and fill differential	ок 🗖	No 🗖
5	Drain, flush and fill planetaries	ок 🗖	No 🗖
6	Check pins and bushings for wear	ок 🗖	No 🗖
7	Steam clean machine, inspect for structural cracks	ок 🗖	No 🗖
8	Replace cab pressurizer and air recirculation elements.	ок 🗖	No 🗖
9	Drivelines - See service form 80-627, Driveline Service & Maintenance.	ок 🗖	No 🗖
10	Have ANSUL representative inspect and recertify fire suppression system	ок 🗖	No 🗖

MECHANIC	
SUPERVISOR	
DATE	
MODEL	
SERIAL No	
HOUR METER	

# Maintenance (1500 Hours), or 1 Year

Perform these checks at 1500 hours, or 1 year, whichever occurs first. Perform all previous maintenance procedures that are due for scheduled maintenance.

1	Adjust overhead set, engine	ок 🗖	No 🗖
2	Check radiator assembly	ок 🗖	No 🗖
3	Check water pump, engine	ок 🗖	No 🗖
4	Check cooling system hoses	ок 🗖	No 🗖
5	Check batteries	ок 🗖	No 🗖
6	Check turbo charger	ок 🗖	No 🗖
7	Check engine Mounts	ок 🗖	No 🗖

# Annual Maintenance (2000 Hours)

Perform these checks annually, or after 2000 hours, whichever occurs first.

1	Repeat the 1,000 hour check	ОК 🗖	No 🗖
2	Change hydraulic oil	ок 🗖	No 🗖
3	Drivelines - Inspect slip splines for wear (backlash). See service form 80-627, Driveline Service & Maintenance	ок 🗖	No 🗖
4	Check wet disc brake lining wear	ок 🗖	No 🗖
5	Inspect wheel bearing preload, readjust if necessary	ок 🗖	Readjust 🗖
6	Perform automatic clutch calibration, transmission	ок 🗖	No 🗖
7	Calibrate transmission control unit. See service form 80-1134.	ОК 🗖	No 🗖
8	Have Allied representative inspect machine (annually)	ОК 🗖	No 🗖

MECHANIC	
SUPERVISOR	
DATE	
MODEL	
SERIAL No	
HOUR METER	

### Wagner

#### Maintenance (6000 Hours), or 2 Years

Perform these checks at 6000 hours, or 2 years, whichever occurs first. Perform all previous maintenance procedures that are due for scheduled maintenance.

1	Check vibration dampener, engine	ок 🗖	No 🗖
2	Check fan drive pulley assembly, engine	ок 🗖	No 🗖
3	Check fan hub, engine	ок 🗖	No 🗖
4	Check air compressor discharge lines	ок 🗖	No 🗖

#### **Overhaul Schedule**

To maximize efficiency and minimize downtime and costly failures, Allied Systems Company recommends the following overhaul chart to be used. When followed closely, your equipment will last longer with less unexpected downtime. Contact your local Wagner dealer for the kits necessary to overhaul your drivetrain components or allow your dealer to overhaul the components for you. They are authorized to overhaul and test your components.

It is recommended that some components be overhauled at the same time, even if they might have some time before their required rebuild, to minimize downtime. Many components may have to be removed in order to gain access to others so the parts should all be rebuilt together. This will save you from having to tear the machine down again a few thousand operation hours later. During the overhaul process, make sure all parts are thoroughly cleaned before installation. Parts that do not receive this cleaning can cause the lubricant to become contaminated, which leads to much shorter service life.

## 

The overhaul schedule below is applicable when all preventive maintenance and oil testing is performed and only when genuine Wagner OEM replacement parts and lubricants are used. Major component overhauls may need to be performed more frequently if preventive maintenance is not performed, non-OEM replacement parts are used, and/or the machine is operated frequently on slopes, uneven terrain, or in poor traction conditions.

Component	Hours
Engine	20,000
Transmission	20,000
Pumps	10,000
Axle	20,000
Brakes	40,000
Hydraulic Cylinders - Reseal	10,000
Hoses and Fittings	20,000

MECHANIC
SUPERVISOR
DATE
MODEL
SERIAL No
HOUR METER

#### INTENTIONALLY LEFT BLANK