



WARNING

IMPORTANT SAFETY INSTRUCTIONS

— DUAL WHEEL ASSEMBLIES —

MOUNTING -- NEVER INFLATE TIRES TO MORE THAN 10 PSI UNTIL THEY ARE SECURELY MOUNTED ON THE VEHICLE AXLE WITH ALL COMPONENTS PROPERLY IN PLACE. USE A CLIP-ON CHUCK AND AN IN-LINE VALVE WITH GAUGE OR A PRE-SET PRESSURE REGULATOR.

STAND CLEAR OF POTENTIAL BLAST AND TRAJECTORY OF THE RIM COMPONENTS DURING TIRE INFLATION.

DEMOUNTING -- ALWAYS EXHAUST ALL PRESSURE FROM BOTH TIRES OF DUAL ASSEMBLIES BEFORE LOOSENING OR REMOVING ANY RIM COMPONENTS OR ATTACHING HARDWARE SUCH AS RIM NUTS AND RIM CLAMPS. REMOVE THE VALVE CORES AND USE A PIECE OF WIRE TO MAKE SURE THAT THE VALVE STEMS ARE NOT PLUGGED.

READ AND FOLLOW THESE SAFETY INSTRUCTIONS. FAILURE TO DO SO COULD RESULT IN SERIOUS INJURY OR DEATH. ALSO SEE SAFETY & SERVICE MANUAL, GOODYEAR PUBLICATION, FORM NO. EM83-2401.