

IMPORTANT!

OPERATIONAL GUIDELINES L-80S EXTENSION SYSTEM

1. RATED LIFT CAPACITY IS 80,000 LBS. AT THE RATED LOAD CENTER WITH THE EXTENSION SYSTEM FULLY RETRACTED AT ANY POSITION OF CARRIAGE AND BOOM.
2. THE EXTENSION SYSTEM WILL RAISE THE TINES 31" AND EXTEND THE CARRIAGE FORWARD 36" FOR HIGHER DECKING.
3. RATED LIFT CAPACITY IS 60,000 LBS. WITH THE EXTENSION SYSTEM FULLY EXTENDED AND CARRIAGE LEVEL. PARTIAL EXTENSION OF THE SYSTEM PROPORTIONATELY REDUCES LOAD CAPACITY. SYSTEM MAY NOT EXTEND IF OVER-LOADED.
4. DO NOT EXTEND CARRIAGE WITH MORE THAN THE RATED LOAD OF 60,000 LBS. OR IF WEIGHT OF LOAD IS UNKNOWN (RECLAIMING FROM DECK). OVER-LOADED CONDITION MAY CAUSE TIPPING.
5. DO NOT ATTEMPT TO USE EXTENSION SYSTEM WHEN CARRIAGE IS IN TILT-BACK POSITION.
6. DO NOT TRAVEL WITH CARRIAGE EXTENDED WHEN FULLY OR PARTIALLY LOADED.

CAUTION: FAILURE TO OBSERVE THESE OPERATING GUIDELINES MAY RESULT IN DAMAGE TO THE MACHINE, AND/OR CREATE A SAFETY HAZARD FOR OPERATIONAL AND GROUND PERSONNEL.