

Lubrication L90F

Proper and consistent lubrication of articulation points on your Wagner is vital to the longevity of your machine.

An optional automatic lubrication system will lubricate most of the points on your Wagner, but inspection of these points is still necessary to ensure the automatic system is working properly. Note: Manual lubrication is always required for the drivelines, and the steering column.

Note: The drivelines require a different grease than the rest of the machine. See Fluids chart in Section 5-2, or the tables on page 5-3-2 for details.

Note: Always refer to manufacturer's (e.g. engine, transmission, axle) maintenance manual before performing any maintenance.




Figure 5-3-1 Lubrication Points

94-1504-04 Rev:09-2015 5-3-1

Lubrication Schedule

Refer to: 5-3-1 & 5-3-2

Refer to: 5-3-1 & 5-3-2		
10 Hours		
Before engine startup, check the following:		
1	Steering Cylinder Pins	Mobilgrease Special No. 2
2	Boom To Chassis Pins	
3	Boom To Carriage Pins *a	
4 & 5	Hoist Cylinder Pins *a	
6 & 7	Tilt Cylinder Pins	
8	Holddown Arm Pins	
9	Kickoff Arm Pins	
10	Holddown Cylinder Pins	
(11)	Kickoff Cylinder Pins	
	50 Hours	
(12)	Driveline Cross Assemblies *b*c (refer to service form 80-627)	Mobilith SHC 220 Grease
16)	Optional Automatic Grease System. Check grease level. See 80-1088 for service and maintenance information.	Mobilgrease Special No. 2
	250 Hours	
18)	Seat Platform Swivel Bearing *c (grease fitting located under cab)	Mobilith SHC 220 Grease
	500 Hours	
14)	Tailwheel Bearing	Mobilgrease Special No. 2
(15)	Tailpost	
	1000 Hours	
13)	Driveline Slip Yokes *b*c (refer to service form 80-627)	Mobilith SHC 220 Grease
	2000 Hours	
17)	Steering Column U-Joints *c	Mobilgrease Special No. 2

^{*}a When operating in water, lubricate submerged points more frequently.

5-3-2 94-1503-04 Rev: 09-2015

^{*}b Use handgun or lower pressure adaptor; lubricate sparingly.

^{*}c Not lubricated by optional automatic grease system.